

## Concerns with Waste to Energy (WtE) plants

### What is the issue?

\n\n

Waste to Energy (WtE) plants in our cities, using inadequately segregated municipal waste as feedstock, are shown to be highly dangerous to the environment.

\n\n

### Why are WtE plants using municipal waste so harmful for us?

\n\n

\n

- There are five municipal WtE plants operational in India, with a total capacity to produce 66.4 MW electricity per day.

\n

- Many cities across different states vying for such plants as a solution to the very complex challenge of solid waste management in urban India.

\n

- But the WtE plants in India burn mixed waste.

\n

- The presence of chlorinated hydrocarbons like PVC in our waste results in the release of dioxins and furans when the waste is burnt at less than 850°C.

\n

- Dioxins and furans are among the most dangerous chemical agents.

\n

- They are known to be carcinogenic and can lead to impairment of immune, endocrine, nervous, and reproductive systems.

\n

- They are also extremely difficult and costly to measure.

\n

- Appropriate filtering mechanisms need to be installed to control such dangerous emissions.

\n

- But the WtE plants in India was being operated without adequate use of activated charcoal for filtering out dioxins, furans and mercury from the emissions.

\n

- Even when incineration takes place under optimal conditions, large amounts of flue gases, mercury vapour and lead compounds are released.
- Additionally, about 30% residue from incineration in the form of slag (bottom ash) and fly ash (particulate matter) getting released, which are also known to be serious pollutants of air and water.

\n\n

## Why are WtE plants inefficient in generating energy in India?

\n\n

- **Moisture content** - Municipal waste in India has a very high biodegradable (wet) waste content ranging anywhere between 60 and 70% of the total, compared with 30% in the West.
- This gives our waste a very high moisture content and very low calorific value.
- **Calorific value** - Also, Indian households have traditionally been recycling their waste such as paper, plastic, cardboard, cloth, rubber, etc., to local recyclers.
- This further lowers the calorific value of our waste, which is about 1000-1300 Kcal/kg.
- In contrast, the calorific value of municipal waste in the West is much higher at about 1900 -2800 Kcal/kg which leads to much higher efficiency in their WtE plants.
- **Mixed waste** - India's Solid Waste Management (SWM) policy requires that wet and dry wastes should not be mixed.
- This will ensure that only non-compostable and non-recyclable wastes with at least 1500 Kcal/kg should reach WtE plants.
- However, such waste comprises only 10-15% of the total waste in India.
- **Compression of waste** - The challenge of segregation at source is compounded by the municipal governments themselves when they use compactors to reduce the transport cost of the waste.
- Compacting compresses the waste and makes even gross segregation at the

plant site impossible.

\n

- In the absence of adequate feedstock of non-compostable and non-recyclable waste, it becomes necessary to use auxiliary fuel, adding to the cost of operating the plants.

\n

- **Implementation delay** - SWM Rules 2016 require that PVC be phased out in incinerators by April 2018.

\n

- But it is impossible to identify and remove PVC beverage labels, for example, from mixed waste streams.

\n

- As a preventive measure, NGT directed the ministry of environment and forests (MoEF) to consider phase out of such single-use, short-life PVC and issue appropriate directions by July 2017.

\n

- But the directions merely remained on paper and was not properly implemented at the ground level.

\n

\n\n

## What should be done?

\n\n

\n

- Waste to Energy plants using municipal solid waste from Indian cities as feedstock pose a serious threat to our health and environment.

\n

- In this regard, Municipal authorities should be made aware that WtE technologies are being phased out in the West.

\n

- They should not be allowed unless the waste offered meets the criterion specified by the SWM Rules 2016.

\n

- Also, it needs to be ensured that the waste is not mixed at the source of generation and then that the handling of waste is done in unmixed streams.

\n

- There should also be strict penalties for non-compliance, when these contracts were outsourced to private operators.

\n

- At the same time, India should also explore low cost options such as composting and bio-methanation as an alternate to WTE plants.

\n

\n\n

\n\n

**Source: Financial Express**

\n

